

SAFETY DATA SHEET

DOW AGROSCIENCES LIMITED

Safety Data Sheet according to Reg. (EU) No 2015/830

Product name: STARANE™ 2 Herbicide

Revision Date: 26.09.2016

Version: 4.3

Print Date: 26.09.2016

DOW AGROSCIENCES LIMITED encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: STARANE™ 2 Herbicide

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Plant Protection Product

1.3 Details of the supplier of the safety data sheet

COMPANY IDENTIFICATION

DOW AGROSCIENCES LIMITED

CPC2 CAPITAL PARK

FULBOURN

CAMBRIDGE

England

CB21 5XE

UNITED KINGDOM

Customer Information Number:

SDSQuestion@dow.com

1.4 EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 0031 115 694 982

Local Emergency Contact: 00 31 115 69 4982

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008:

Flammable liquids - Category 3 - H226

Skin irritation - Category 2 - H315

Eye irritation - Category 2 - H319

Skin sensitisation - Category 1 - H317

Aspiration hazard - Category 1 - H304

Specific target organ toxicity - single exposure - Category 3 - Respiratory tract irritant. - H335

Specific target organ toxicity - single exposure - Category 3 - Narcotic effects. - H336

Acute aquatic toxicity - Category 1 - H400

Chronic aquatic toxicity - Category 1 - H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

Hazard pictograms



Signal word: DANGER

Hazard statements

| | |
|------|---|
| H226 | Flammable liquid and vapour. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H317 | May cause an allergic skin reaction. |
| H304 | May be fatal if swallowed and enters airways. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H410 | Very toxic to aquatic life with long lasting effects. |

Precautionary statements

| | |
|-----------------------|---|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. No smoking. |
| P280 | Wear protective gloves/ protective clothing/ eye protection/ face protection. |
| P301 + P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor. |
| P302 + P352 | IF ON SKIN: Wash with plenty of soap and water. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P331 | Do NOT induce vomiting. |
| P501 | Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste. |

Supplemental information

| | |
|--------|---|
| EUH401 | To avoid risks to human health and the environment, comply with the instructions for use. |
|--------|---|

Contains Hydrocarbons, C9, aromatics; Hydrocarbons, C10, aromatics, <1% naphthalene

2.3 Other hazards

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

This product is a mixture.

| CASRN / EC-No. / Index-No. | REACH Registration Number | Concentration | Component | Classification: REGULATION (EC) No 1272/2008 |
|--|--|----------------------|--|---|
| CASRN 81406-37-3 EC-No. 279-752-9 Index-No. 607-272-00-5 | — | 29.7% | fluoroxypyr-meptyl (ISO) | Aquatic Acute - 1 - H400 Aquatic Chronic - 1 - H410 |
| CASRN Not available EC-No. 918-668-5 Index-No. — | 01-2119455851-35 | > 60.0 - < 70.0 % | Hydrocarbons, C9, aromatics | Flam. Liq. - 3 - H226 STOT SE - 3 - H336 STOT SE - 3 - H335 Asp. Tox. - 1 - H304 Aquatic Chronic - 2 - H411 |
| CASRN 68953-96-8 EC-No. 273-234-6 Index-No. — | 01-2119964467-24 | < 5.0 % | Benzenesulfonic acid, mono-C11-13- branched alkyl derivs., calcium salts | Acute Tox. - 4 - H312 Skin Irrit. - 2 - H315 Eye Dam. - 1 - H318 Aquatic Chronic - 2 - H411 |
| CASRN 111-27-3 EC-No. 203-852-3 Index-No. 603-059-00-6 | 01-2119487967-12 | < 5.0 % | Hexan-1-ol | Flam. Liq. - 3 - H226 Acute Tox. - 4 - H302 Eye Irrit. - 2 - H319 STOT SE - 3 - H336 |
| CASRN Not Available EC-No. 918-811-1 Index-No. — | 01-2119463583-34 | < 1.0 % | Hydrocarbons, C10, aromatics, <1% naphthalene | STOT SE - 3 - H336 Asp. Tox. - 1 - H304 Aquatic Chronic - 2 - H411 |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If person is not breathing, call an emergency responder or ambulance, then give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask etc). Call a poison control center or doctor for treatment advice. If breathing is difficult, oxygen should be administered by qualified personnel.

Skin contact: Take off contaminated clothing. Wash skin with soap and plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. Wash clothing before reuse. Shoes and other leather items which cannot be decontaminated should be disposed of properly.

Eye contact: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a poison control center or doctor for treatment advice. Suitable emergency eye wash facility should be available in work area.

Ingestion: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: Skin contact may aggravate preexisting dermatitis. Maintain adequate ventilation and oxygenation of the patient. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. The decision of whether to induce vomiting or not should be made by a physician. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Have the Safety Data Sheet, and if available, the product container or label with you when calling a poison control center or doctor, or going for treatment.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: No data available

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Hydrogen fluoride.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is produced when product burns.

5.3 Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Consider feasibility of a controlled burn to minimize environment damage. Foam fire extinguishing system is preferred because uncontrolled water can spread possible contamination. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

6.2 Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. Spills or discharge to natural waterways is likely to kill aquatic organisms.

6.3 Methods and materials for containment and cleaning up: Contain spilled material if possible. Pump with explosion-proof equipment. If available, use foam to smother or suppress. Small spills: Absorb with materials such as: Clay. Dirt. Sand. Sweep up. Collect in suitable and properly labeled containers. Large spills: Contact Dow AgroSciences for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

6.4 Reference to other sections: References to other sections, if applicable, have been provided in the previous sub-sections.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: Keep out of reach of children. Keep away from heat, sparks and flame. Do not swallow. Avoid contact with eyes, skin, and clothing. Avoid breathing vapor or mist. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Keep container closed. Use with adequate ventilation. No smoking, open flames or sources of ignition in handling and storage area. Electrically ground and bond all equipment. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

7.2 Conditions for safe storage, including any incompatibilities: Store in a dry place. Store in original container. Keep container tightly closed when not in use. Do not store near food, foodstuffs, drugs or potable water supplies. Minimize sources of ignition, such as static build-up, heat, spark or flame.

Storage stability

To maintain product quality, recommended storage temperature is $> 0\text{ }^{\circ}\text{C}$

7.3 Specific end use(s): Refer to product label.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure limits are listed below, if they exist.

| Component | Regulation | Type of listing | Value/Notation |
|--------------------------|------------|-----------------|----------------------|
| fluoroxypyr-meptyl (ISO) | Dow IHG | TWA | 10 mg/m ³ |
| Hexan-1-ol | US WEEL | TWA | 40 ppm |
| | Dow IHG | TWA | 50 ppm |

RECOMMENDATIONS IN THIS SECTION ARE FOR MANUFACTURING, COMMERCIAL BLENDING AND PACKAGING WORKERS. APPLICATORS AND HANDLERS SHOULD SEE THE PRODUCT LABEL FOR PROPER PERSONAL PROTECTIVE EQUIPMENT AND CLOTHING.

8.2 Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent.

Skin protection

Hand protection: Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Styrene/butadiene rubber. Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl").

When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. If vapors are strong enough to be irritating to the nose, or eyes, the OEL is probably being exceeded. Special ventilation or respiratory protection may be required.

Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

Environmental exposure controls

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

| | |
|--------------------------|--|
| Physical state | Liquid. |
| Color | Brown |
| Odor | Aromatic |
| Odor Threshold | No test data available |
| pH | 5.3 1% CIPAC MT 75.2 (1% aqueous suspension) |
| Melting point/range | Not applicable |
| Freezing point | No test data available |
| Boiling point (760 mmHg) | No test data available |
| Flash point | closed cup 55 °C CIPAC MT 12 |

| | |
|---|---|
| Evaporation Rate (Butyl Acetate = 1) | No test data available |
| Flammability (solid, gas) | Not Applicable |
| Lower explosion limit | No test data available |
| Upper explosion limit | No test data available |
| Vapor Pressure | No test data available |
| Relative Vapor Density (air = 1) | No test data available |
| Relative Density (water = 1) | 0.9698 at 20 °C <i>Pyknometer</i> |
| Water solubility | emulsifiable |
| Partition coefficient: n-octanol/water | No data available |
| Auto-ignition temperature | 442 °C <i>EC Method A15</i> |
| Decomposition temperature | No test data available |
| Dynamic Viscosity | No test data available |
| Kinematic Viscosity | 2.96 mm ² /s at 20 °C <i>ASTM D455</i> |
| Explosive properties | No No <i>EEC A14</i> |
| Oxidizing properties | No test data available |

9.2 Other information

| | |
|-------------------------|---|
| Liquid Density | 0.9698 g/cm ³ at 20 °C <i>Pyknometer</i> |
| Molecular weight | No data available |
| Surface tension | 27.0 mN/m at 25 °C <i>EC Method A5</i> |

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: No dangerous reaction known under conditions of normal use.

10.2 Chemical stability: Thermally stable at typical use temperatures.

10.3 Possibility of hazardous reactions: Polymerization will not occur.

10.4 Conditions to avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems. Avoid direct sunlight.

10.5 Incompatible materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

10.6 Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Toxic gases are released during decomposition.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

As product:

LD50, Rat, male, > 2,000 - 3,500 mg/kg

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product:

LD50, Rat, male and female, > 5,000 mg/kg

Acute inhalation toxicity

Vapor concentrations are attainable which could be hazardous on single exposure. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness.

As product: The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause severe skin irritation with pain and local redness.

May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause pain disproportionate to the level of irritation to eye tissues.

May cause moderate eye irritation.

May cause slight corneal injury.

Sensitization

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause respiratory irritation.

May cause drowsiness or dizziness.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

For the active ingredient(s):

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Based on information for component(s):

In animals, effects have been reported on the following organs:

Eye.

Gastrointestinal tract.

Respiratory tract.

Carcinogenicity

For the active ingredient(s): Did not cause cancer in laboratory animals.

For the minor component(s): Has caused cancer in laboratory animals. However, the relevance of this to humans is unknown.

Teratogenicity

For the active ingredient(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

For the solvent(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Has caused birth defects in laboratory animals only at doses producing severe toxicity in the mother.

Reproductive toxicity

For the solvent(s): In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. In animal studies, active ingredient did not interfere with reproduction.

Mutagenicity

For the active ingredient(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

May be fatal if swallowed and enters airways.

COMPONENTS INFLUENCING TOXICOLOGY:**fluoroxypyr-meptyl (ISO)****Acute inhalation toxicity**

Prolonged exposure is not expected to cause adverse effects. Dust may cause irritation to upper respiratory tract (nose and throat).

Maximum attainable concentration. LC50, Rat, male and female, 4 Hour, dust/mist, > 1.16 mg/l No deaths occurred at this concentration.

Hydrocarbons, C9, aromatics**Acute inhalation toxicity**

Vapor concentrations are attainable which could be hazardous on single exposure. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness.

LC50, Rat, 4 Hour, vapour, > 10.2 mg/l

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts**Acute inhalation toxicity**

The LC50 has not been determined.

Hexan-1-ol**Acute inhalation toxicity**

No adverse effects are anticipated from single exposure to vapor. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs.

LC50, Rat, male and female, 1 Hour, vapour, > 21 mg/l No deaths occurred at this concentration.

Hydrocarbons, C10, aromatics, <1% naphthalene

Acute inhalation toxicity

Prolonged excessive exposure may cause adverse effects. May cause central nervous system effects. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs.

As product: The LC50 has not been determined.

For similar material(s): LC50, Rat, 4 Hour, vapour, > 4.688 mg/l

Maximum attainable concentration.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

12.1 Toxicity

Acute toxicity to fish

Material is very toxic to aquatic organisms (LC50/EC50/IC50 below 1 mg/L in the most sensitive species).

LC50, *Oncorhynchus mykiss* (rainbow trout), flow-through test, 96 Hour, 8.5 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna* (Water flea), flow-through test, 48 Hour, 6.2 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

ErC50, *Pseudokirchneriella subcapitata* (green algae), static test, 72 Hour, > 40 mg/l, OECD Test Guideline 201

ErC50, diatom *Navicula* sp., Static, 72 Hour, 0.684 mg/l, OECD Test Guideline 201

Toxicity to Above Ground Organisms

Material is practically non-toxic to birds on an acute basis (LD50 > 2000 mg/kg).

oral LD50, *Colinus virginianus* (Bobwhite quail), mortality, > 2250mg/kg bodyweight.

contact LD50, *Apis mellifera* (bees), 48 Hour, mortality, > 100µg/bee

oral LD50, *Apis mellifera* (bees), 48 Hour, mortality, > 130µg/bee

Toxicity to soil-dwelling organisms

LC50, *Eisenia fetida* (earthworms), 14 d, survival, 270 mg/kg

12.2 Persistence and degradability

fluoroxypyr-meptyl (ISO)

Biodegradability: Material is not readily biodegradable according to OECD/EEC guidelines.

10-day Window: Fail

Biodegradation: 32 %

Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

Theoretical Oxygen Demand: 2.2 mg/mg

Stability in Water (1/2-life)

Hydrolysis, half-life, 454 d

Hydrocarbons, C9, aromatics

Biodegradability: For the major component(s): Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability. For some component(s): Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail

Biodegradation: 2.9 %

Exposure time: 28 d

Method: OECD Test Guideline 301E or Equivalent

Hexan-1-ol

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 61 %

Exposure time: 30 d

Method: OECD Test Guideline 301D or Equivalent

10-day Window: Pass

Biodegradation: 77 %

Exposure time: 30 d

Method: OECD Test Guideline 301D or Equivalent

Hydrocarbons, C10, aromatics, <1% naphthalene

Biodegradability: Material is inherently biodegradable (reaches > 20% biodegradation in OECD test(s) for inherent biodegradability).

12.3 Bioaccumulative potential

fluoroxypyr-meptyl (ISO)

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 5.04 Measured

Bioconcentration factor (BCF): 26 Oncorhynchus mykiss (rainbow trout) Measured

Hydrocarbons, C9, aromatics

Bioaccumulation: For the major component(s): Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5). For the minor component(s): Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 4.6 OECD Test Guideline 107 or Equivalent

Hexan-1-ol

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1.8 Measured

Hydrocarbons, C10, aromatics, <1% naphthalene

Bioaccumulation: No data available for this product. For similar material(s): Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

12.4 Mobility in soil**fluoroxypyr-meptyl (ISO)**

Expected to be relatively immobile in soil (Koc > 5000).

Partition coefficient (Koc): 6200 - 43000

Hydrocarbons, C9, aromatics

No relevant data found.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts

No relevant data found.

Hexan-1-ol

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 8.3

Hydrocarbons, C10, aromatics, <1% naphthalene

No relevant data found.

12.5 Results of PBT and vPvB assessment**fluoroxypyr-meptyl (ISO)**

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Hydrocarbons, C9, aromatics

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Hexan-1-ol

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Hydrocarbons, C10, aromatics, <1% naphthalene

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

12.6 Other adverse effects**fluoroxypyr-meptyl (ISO)**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Hydrocarbons, C9, aromatics

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Hexan-1-ol

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Hydrocarbons, C10, aromatics, <1% naphthalene

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

If wastes and/or containers cannot be disposed of according to the product label directions, disposal of this material must be in accordance with your local or area regulatory authorities. This information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. If the material as supplied becomes a waste, follow all applicable regional, national and local laws.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

SECTION 14: TRANSPORT INFORMATION

Classification for ROAD and Rail transport (ADR/RID):

| | |
|--|--|
| 14.1 UN number | UN 1993 |
| 14.2 UN proper shipping name | FLAMMABLE LIQUID, N.O.S.(Aromatic hydrocarbon) |
| 14.3 Transport hazard class(es) | 3 |
| 14.4 Packing group | III |
| 14.5 Environmental hazards | Fluroxypyr 1-methylheptyl ester |
| 14.6 Special precautions for user | Special Provision 640E Hazard Identification Number: 30 |

Classification for SEA transport (IMO-IMDG):

| | |
|---|--|
| 14.1 UN number | UN 1993 |
| 14.2 UN proper shipping name | FLAMMABLE LIQUID, N.O.S.(Aromatic hydrocarbon) |
| 14.3 Transport hazard class(es) | 3 |
| 14.4 Packing group | III |
| 14.5 Environmental hazards | Fluroxypyr 1-methylheptyl ester |
| 14.6 Special precautions for user | EmS: F-E, S-E |
| 14.7 Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code | Consult IMO regulations before transporting ocean bulk |

Classification for AIR transport (IATA/ICAO):

| | |
|-----------------------------------|--|
| 14.1 UN number | UN 1993 |
| 14.2 UN proper shipping name | Flammable liquid, n.o.s.(Aromatic hydrocarbon) |
| 14.3 Transport hazard class(es) | 3 |
| 14.4 Packing group | III |
| 14.5 Environmental hazards | Not applicable |
| 14.6 Special precautions for user | No data available. |

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**REACH Regulation (EC) No 1907/2006**

This product contains only components that have been either pre-registered, registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH). The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: FLAMMABLE LIQUIDS

Number in Regulation: P5c

5,000 t

50,000 t

Listed in Regulation: ENVIRONMENTAL HAZARDS

Number in Regulation: E1

100 t

200 t

Listed in Regulation: Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Number in Regulation: 34

2,500 t

25,000 t

Other regulations

Registration Number: MAPP 12018

15.2 Chemical safety assessment

For proper and safe use of this product, please refer to the approval conditions laid down on the product label.

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

| | |
|------|---|
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Flam. Liq. - 3 - H226 - On basis of test data.

Skin Irrit. - 2 - H315 - On basis of test data.

Eye Irrit. - 2 - H319 - On basis of test data.

Skin Sens. - 1 - H317 - On basis of test data.

Asp. Tox. - 1 - H304 - On basis of test data.
STOT SE - 3 - H335 - Calculation method
STOT SE - 3 - H336 - Calculation method
Aquatic Acute - 1 - H400 - On basis of test data.
Aquatic Chronic - 1 - H410 - Calculation method

Revision

Identification Number: 101202953 / A293 / Issue Date: 26.09.2016 / Version: 4.3

DAS Code: EF-1512

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

| | |
|---------|---|
| Dow IHG | Dow Industrial Hygiene Guideline |
| TWA | Time weighted average |
| US WEEL | USA. Workplace Environmental Exposure Levels (WEEL) |

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW AGROSCIENCES LIMITED urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.